

Diagonal 8.86 mm (Type 1/1.8) CMOS Solid-state Image Sensor with Square Pixel for Color Cameras

IMX678-AAQR1-C

STARVIS 2

Description

The IMX678-AAQR1-C is a diagonal 8.86 mm (Type 1/1.8) CMOS active pixel type solid-state image sensor with a square pixel array and 8.40 M effective pixels. This chip operates with analog 3.3 V, digital 1.1 V, and interface 1.8 V triple power supply, and has low power consumption. High sensitivity, low dark current and no smear are achieved through the adoption of R, G and B primary color mosaic filters. This chip features an electronic shutter with variable charge-integration time.

(Application: Security cameras)

Features

- ◆ CMOS active pixel type dots
- ◆ Built-in timing adjustment circuit, H/V driver and serial communication circuit
- ◆ Input frequency: 13.5 MHz / 18 MHz / 24 MHz / 27 MHz / 36 MHz / 37.125 MHz / 72 MHz / 74.25 MHz
- ◆ Number of recommended recording pixels: 3840 (H) × 2160 (V) approx. 8.29M pixel
- ◆ Readout mode
 - All-pixel scan mode
 - Horizontal / Vertical 2/2-line binning mode
 - Window cropping mode
 - Horizontal / Vertical direction - Normal / Inverted readout mode
- ◆ Readout rate
 - Maximum frame rate in
 - All-pixel scan mode: 12 bit: 60 frame/s, 10 bit: 60 frame/s
- ◆ High dynamic range (HDR) function
 - Digital overlap HDR
 - Clear HDR
- ◆ Synchronizing sensors function
- ◆ Variable-speed shutter function (resolution 1H unit)
- ◆ Conversion gain switching (HCG Mode / LCG Mode)
- ◆ CDS / PGA function
 - 0 dB to 30 dB: Analog Gain 30 dB (step pitch 0.3 dB)
 - 30.3 dB to 72 dB: Analog Gain 30 dB + Digital Gain 0.3 dB to 42 dB (step pitch 0.3 dB)
- ◆ Supports I/O
 - CSI-2 serial data output (2 Lane / 4 Lane / 8Lane / 4Lane × 2ch)
 - RAW10 / RAW12 output

Sony Semiconductor Solutions Corporation reserves the right to change products and specifications without prior notice.

This information does not convey any license by any implication or otherwise under any patents or other right.

Application circuits shown, if any, are typical examples illustrating the operation of the devices. Sony Semiconductor Solutions Corporation cannot assume responsibility for any problems arising out of the use of these circuits.

Device Structure

- ◆ CMOS image sensor
- ◆ Image size
Diagonal 8.86 mm (Type 1/1.8) approx. 8.40 M pixels, All pixels
- ◆ Total number of pixels
3856 (H) × 2200 (V) approx. 8.48 M pixels
- ◆ Number of effective pixels
3856 (H) × 2180 (V) approx. 8.40 M pixels
- ◆ Number of active pixels
3856 (H) × 2176 (V) approx. 8.39 M pixels
- ◆ Number of recommended recording pixels
3840 (H) × 2160 (V) approx. 8.29 M pixels
- ◆ Unit cell size
2.0 μm (H) × 2.0 μm (V)
- ◆ Optical black
Horizontal (H) direction: Front 0 pixels, rear 0 pixels
Vertical (V) direction: Front 20 pixels, rear 0 pixels
- ◆ Substrate material
Silicon

Maison Technologies Ltd.
Internal use only

Absolute Maximum Ratings

Item	Symbol	Min.	Max.	Unit	Remarks
Supply voltage (analog: 3.3 V)	AV _{DD}	-0.3	3.65	V	—
Supply voltage (interface: 1.8 V)	OV _{DD}	-0.3	3.65	V	—
Supply voltage (digital: 1.1 V)	DV _{DD}	-0.3	2.0	V	—
Input voltage	VI	-0.3	OV _{DD} + 0.3	V	Not exceed 3.3 V
Output voltage	VO	-0.3	OV _{DD} + 0.3	V	Not exceed 3.3 V
Operating temperature	Topr	-30	85	°C	—
Storage temperature	Tstg	-40	85	°C	—

Application Conditions

Item	Symbol	Min.	Typ.	Max.	Unit
Supply voltage (analog: 3.3 V)	AV _{DD}	3.20	3.30	3.40	V
Supply voltage (interface: 1.8 V)	OV _{DD}	1.70	1.80	1.90	V
Supply voltage (digital: 1.1 V)	DV _{DD}	1.00	1.10	1.20	V
Performance guarantee temperature	Tspec	-10	—	60	°C

Maison Technologies Ltd.
Internal use only

USE RESTRICTION NOTICE

This USE RESTRICTION NOTICE ("Notice") is for customers who are considering or currently using the image sensor products ("Products") set forth in this specifications book. Sony Semiconductor Solutions Corporation ("SSS") may, at any time, modify this Notice which will be available to you in the latest specifications book for the Products. You should abide by the latest version of this Notice. If a SSS subsidiary or distributor has its own use restriction notice on the Products, such a use restriction notice will additionally apply between you and the subsidiary or distributor. You should consult a sales representative of the subsidiary or distributor of SSS on such a use restriction notice when you consider using the Products.

Use Restrictions

- The Products are intended for incorporation into such general electronic equipment as office products, communication products, measurement products, and home electronics products in accordance with the terms and conditions set forth in this specifications book and otherwise notified by SSS from time to time.
- You should not use the Products for critical applications which may pose a life- or injury-threatening risk or are highly likely to cause significant property damage in the event of failure of the Products. You should consult your sales representative beforehand when you consider using the Products for such critical applications. In addition, you should not use the Products in weapon or military equipment.
- SSS disclaims and does not assume any liability and damages arising out of misuse, improper use, modification, use of the Products for the above-mentioned critical applications, weapon and military equipment, or any deviation from the requirements set forth in this specifications book.

Design for Safety

- SSS is making continuous efforts to further improve the quality and reliability of the Products; however, failure of a certain percentage of the Products is inevitable. Therefore, you should take sufficient care to ensure the safe design of your products such as component redundancy, anti-conflagration features, and features to prevent mis-operation in order to avoid accidents resulting in injury or death, fire or other social damage as a result of such failure.

Export Control

- If the Products are controlled items under the export control laws or regulations of various countries, approval may be required for the export of the Products under the said laws or regulations. You should be responsible for compliance with the said laws or regulations.

No License Implied

- The technical information shown in this specifications book is for your reference purposes only. The availability of this specifications book shall not be construed as giving any indication that SSS and its licensors will license any intellectual property rights in such information by any implication or otherwise. SSS will not assume responsibility for any problems in connection with your use of such information or for any infringement of third-party rights due to the same. It is therefore your sole legal and financial responsibility to resolve any such problems and infringement.

Governing Law

- This Notice shall be governed by and construed in accordance with the laws of Japan, without reference to principles of conflict of laws or choice of laws. All controversies and disputes arising out of or relating to this Notice shall be submitted to the exclusive jurisdiction of the Tokyo District Court in Japan as the court of first instance.

Other Applicable Terms and Conditions

- The terms and conditions in the SSS additional specifications, which will be made available to you when you order the Products, shall also be applicable to your use of the Products as well as to this specifications book. You should review those terms and conditions when you consider purchasing and/or using the Products.

Contents

Description	1
Features	1
Device Structure	2
Absolute Maximum Ratings	3
Application Conditions	3
USE RESTRICTION NOTICE	4
Optical Center	7
Pixel Arrangement	8
Block Diagram and Pin Configuration	9
Pin Description	11
Electrical Characteristics	14
DC Characteristics	14
Current Consumption	15
AC Characteristics	16
Master Clock Waveform (INCK)	16
System Clear (XCLR)	17
XVS / XHS Input Characteristics in Slave Mode (XMASTER pin = High)	18
XVS / XHS Output Characteristics in Master Mode (XMASTER pin = Low)	18
Serial Communication	19
I/O Equivalent Circuit Diagram	21
Spectral Sensitivity Characteristics	22
Image Sensor Characteristics	23
Image Sensor Characteristics Measurement Method	24
Measurement Conditions	24
Color Coding of Physical Pixel Array	24
Definition of standard imaging conditions	24
Measurement Method	25
Setting Registers Using Serial Communication	26
Description of Setting Registers (I ² C)	26
Register Communication Timing (I ² C)	27
Communication Protocol	28
Register Write and Read (I ² C)	29
Single Read from Random Location	29
Single Read from Current Location	29
Sequential Read Starting from Random Location	30
Sequential Read Starting from Current Location	30
Single Write to Random Location	31
Sequential Write Starting from Random Location	31
Register Map	32
Readout Drive mode	33
Image Data Output Format (CSI-2 output)	33
Frame Format	33
Frame Structure	33
Embedded Data Line	34
All-pixel mode	36
Horizontal/Vertical 2/2-line binning mode	38
Description of Various Function	40
Other Function	40
Power-on and Power-off Sequence	41
Power-on sequence	41
Slew Rate Limitation of Power-on Sequence	42
Power-off sequence	43
Sensor Setting Flow	44
Setting Flow in Sensor Slave Mode	44
Setting Flow in Sensor Master Mode	45
Peripheral Circuit	46
Spot Pixel Specifications	47
Zone Definition	47

Notice on White Pixels Specifications 48

Measurement Method for Spot Pixels 49

Spot Pixel Pattern Specification 50

Marking 51

Notes On Handling 52

Package Outline 54


List of Trademark Logos and Definition Statements 55

Revision History 56

Maison Technologies Ltd.
Internal use only


Optical Center

Top View



Pixel Arrangement


Top View




- * Reference pin number is consecutive numbering of package pin array.
See the Pin Configuration for the number of each pin.
The last Effective line and column are not read-out.

Pixel Arrangement

Block Diagram and Pin Configuration



Block Diagram



*The N.C. pin with (GND) can be connected to GND.

Pin Configuration

Pin Description

No.	Pin No	I/O	Analog / Digital	Symbol	Description
1	A1	—	—	N.C.	GND connectable
2	A3	O	D	DMO8P	CSI-2 output
3	A4	Power	D	VDDLSC	1.1 V power supply
4	A5	—	—	N.C.	GND connectable
5	A6	—	—	N.C.	GND connectable
6	A7	—	—	N.C.	GND connectable
7	A8	—	—	N.C.	GND connectable
8	A9	—	—	N.C.	GND connectable
9	A10	—	—	N.C.	GND connectable
10	A12	—	—	N.C.	GND connectable
11	B3	O	D	DMO8N	CSI-2 output
12	B4	GND	D	VSSLSC	1.1 V / 1.8 V GND
13	B5	—	—	N.C.	GND connectable
14	B6	—	—	N.C.	GND connectable
15	B7	—	—	N.C.	GND connectable
16	B8	—	—	N.C.	GND connectable
17	B9	—	—	N.C.	GND connectable
18	B10	—	—	N.C.	GND connectable
19	C1	O	D	DMO6P	CSI-2 output
20	C2	O	D	DMO6N	CSI-2 output
21	C3	GND	D	VSSLSC	1.1 V / 1.8 V GND
22	C4	O	A	VRLSTR	Capacitor connection
23	C5	Power	A	VRHT	Capacitor connection
24	C6	GND	A	VSSHXP	3.3 V GND
25	C7	O	A	VLOADLM	Capacitor connection
26	C8	O	A	TVMON2	TEST output pin, OPEN
27	C9	O	A	TVMON1	TEST output pin, OPEN
28	C10	—	—	N.C.	GND connectable
29	C11	GND	D	VSSLSC	1.1 V / 1.8 V GND
30	C12	Power	D	VDDLSC	1.1 V power supply
31	D1	O	D	DCK2P	CSI-2 clock output
32	D2	O	D	DCK2N	CSI-2 clock output
33	D3	GND	D	VSSLSC	1.1 V / 1.8 V GND
34	D4	GND	A	VSSHXP	3.3 V GND
35	D5	GND	A	VSSHDA1	3.3 V GND
36	D6	GND	A	VSSHCP1	3.3 V GND
37	D7	GND	A	VSSHXP	3.3 V GND
38	D8	GND	A	VSSHXP	3.3 V GND
39	D9	GND	A	VSSHXP	3.3 V GND
40	D10	—	—	N.C.	GND connectable
41	D11	GND	D	VSSLCN	1.1 V / 1.8 V GND
42	D12	Power	D	VDDLSCN	1.1 V power supply
43	E1	O	D	DMO5P	CSI-2 output
44	E2	O	D	DMO5N	CSI-2 output

No.	Pin No	I/O	Analog / Digital	Symbol	Description
45	E3	Power	D	VDDMIF	1.8 V power supply
46	E4	O	A	VRLF	Capacitor connection
47	E5	Power	A	VDDHDA	3.3 V power supply
48	E6	Power	A	VDDHCP	3.3 V power supply
49	E7	Power	A	VDDHPX	3.3 V power supply
50	E8	Power	A	VDDSUB	3.3 V power supply
51	E9	Power	A	VDDHCM	3.3 V power supply
52	E10	—	—	N.C.	GND connectable
53	E11	GND	D	VSSLSC	1.1 V / 1.8 V GND
54	E12	Power	D	VDDMIO2	1.8 V power supply
55	F1	O	D	DMO7P	CSI-2 output
56	F2	O	D	DMO7N	CSI-2 output
57	F3	GND	D	VSSLSC	1.1 V / 1.8 V GND
58	F4	—	—	N.C.	GND connectable
59	F9	—	—	N.C.	GND connectable
60	F10	I	D	XCLR	System clear
61	F11	I/O	D	SCL	Serial clock input
62	F12	I/O	D	SDA	Serial data communication
63	G1	Power	D	VDDLSC	1.1 V power supply
64	G2	GND	D	VSSLSC	1.1 V / 1.8 V GND
65	G3	Power	D	VDDLIF	1.1 V power supply
66	G4	—	—	N.C.	GND connectable
67	G9	—	—	N.C.	GND connectable
68	G10	I	D	SLAMODE0	Reference pin, Select slave address
69	G11	I	D	XMASTER	Master / Slave selection Slave Mode: High Master Mode: Low
70	G12	I	D	SLAMODE1	Reference pin, Select slave address
71	H1	O	D	DMO4P	CSI-2 output
72	H2	O	D	DMO4N	CSI-2 output
73	H3	GND	D	VSSLSC	1.1 V / 1.8 V GND
74	H4	—	—	N.C.	GND connectable
75	H9	—	—	N.C.	GND connectable
76	H10	I/O	D	TOUT0	TEST output pin, OPEN
77	H11	I/O	D	TOUT1	TEST output pin, OPEN
78	H12	I	D	TENABLE	Test enable, OPEN
79	J1	O	D	DMO2P	CSI-2 output
80	J2	O	D	DMO2N	CSI-2 output
81	J3	Power	D	VDDMIF	1.8 V power supply
82	J4	Power	A	VDDLPL1	1.1 V power supply
83	J5	GND	A	VSSLPL1	1.1 V / 1.8 V GND
84	J6	Power	A	VDDHPX	3.3 V power supply
85	J7	—	—	N.C.	GND connectable
86	J8	Power	A	VDDHPX	3.3 V power supply
87	J9	Power	A	VDDHCM	3.3 V power supply
88	J10	—	—	N.C.	GND connectable

No.	Pin No	I/O	Analog / Digital	Symbol	Description
89	J11	I/O	D	XVS	Vertical sync signal
90	J12	I/O	D	XHS	Horizontal sync signal
91	K1	O	D	DCK1P	CSI-2 clock output
92	K2	O	D	DCK1N	CSI-2 clock output
93	K3	GND	D	VSSLSC	1.1 V / 1.8 V GND
94	K4	Power	A	VDDLPL2	1.1 V power supply
95	K5	GND	A	VSSLPL2	1.1 V / 1.8 V GND
96	K6	GND	A	VSSHPX	3.3 V GND
97	K7	—	—	N.C.	GND connectable
98	K8	GND	A	VSSHPX	3.3 V GND
99	K9	GND	A	VSSHPX	3.3 V GND
100	K10	—	—	N.C.	GND connectable
101	K11	GND	D	VSSLCN	1.1 V / 1.8 V GND
102	K12	Power	D	VDDLCN	1.1 V power supply
103	L1	O	D	DMO1P	CSI-2 output
104	L2	O	D	DMO1N	CSI-2 output
105	L3	GND	D	VSSLSC	1.1 V / 1.8 V GND
106	L4	—	—	N.C.	GND connectable
107	L5	—	—	N.C.	GND connectable
108	L6	—	—	N.C.	GND connectable
109	L7	—	—	N.C.	GND connectable
110	L8	—	—	N.C.	GND connectable
111	L9	—	—	N.C.	GND connectable
112	L10	—	—	N.C.	GND connectable
113	L11	GND	D	VSSLSC	1.1 V / 1.8 V GND
114	L12	Power	D	VDDLSC	1.1 V power supply
115	M3	O	D	DMO3N	CSI-2 output
116	M4	GND	D	VSSLSC	1.1 V / 1.8 V GND
117	M5	GND	A	VSSLPL1	1.1 V / 1.8 V GND
118	M6	GND	A	VSSLPL1	1.1 V / 1.8 V GND
119	M7	—	—	N.C.	GND connectable
120	M8	—	—	N.C.	GND connectable
121	M9	—	—	N.C.	GND connectable
122	M10	—	—	N.C.	GND connectable
123	N1	—	—	N.C.	GND connectable
124	N3	O	D	DMO3P	CSI-2 output
125	N4	Power	D	VDDLSC	1.1 V power supply
126	N5	Power	D	VDDMIO1	1.8 V power supply
127	N6	I	D	INCK	Master clock input
128	N7	—	—	N.C.	GND connectable
129	N8	—	—	N.C.	GND connectable
130	N9	—	—	N.C.	GND connectable
131	N10	—	—	N.C.	GND connectable
132	N12	—	—	N.C.	GND connectable

Electrical Characteristics

DC Characteristics

Item		Pins	Symbol	Condition	Min.	Typ.	Max.	Unit
Supply voltage	Analog	VDDHx VDDSUB	AV _{DD}	—	3.20	3.30	3.40	V
	Interface	VDDMx	OV _{DD}	—	1.70	1.80	1.90	V
	Digital	VDDLx	DV _{DD}	—	1.00	1.10	1.20	V
Digital input voltage		XHS XVS XCLR INCK XMASTER SLAMODE0 SLAMODE1 SDA SCL	VIH	XVS / XHS Slave Mode	$0.8 \times OV_{DD}$	—	—	V
			VIL		—	—	$0.2 \times OV_{DD}$	V
Digital output voltage		XHS XVS TOUT0 TOUT1	VOH	XVS / XHS Master Mode	$OV_{DD} - 0.2$	—	—	V
			VOL		—	—	0.2	V

Current Consumption

Item	Symbol	Typ.	Max.	Unit
Operating current MIPI CSI-2 / 4Lane × 2ch, 1188 Mbps 12 bit, 60 frame/s All-pixel mode	I _{AVDD}	69	86	mA
	I _{OVDD}	4	5	mA
	I _{DVDD}	162	175	mA
Standby current	I _{AVDD_STB}	—	0.3	mA
	I _{OVDD_STB}	—	0.1	mA
	I _{DVDD_STB}	—	28	mA


Operating current: (Typ.) Supply voltage 3.3 V / 1.8 V / 1.1 V, T_j = 25 °C, standard luminous intensity.
(Max.) Supply voltage 3.4 V / 1.9 V / 1.2 V, T_j = 60 °C, worst state of internal circuit
operating current consumption,

Standby: (Max.) Supply voltage 3.4 V / 1.9 V / 1.2 V, T_j = 60 °C, INCK: 0 V, light-obstructed state.

Maison Technologies Ltd.
Internal use only

AC Characteristics

Master Clock Waveform (INCK)



INCK 37.125 MHz, 72 MHz, 74.25 MHz

Item	Symbol	Min.	Typ.	Max.	Unit	Remarks
INCK clock frequency	f_{INCK}	$f_{INCK} \times 0.96$	f_{INCK}	$f_{INCK} \times 1.02$	MHz	$f_{INCK} = 37.125 \text{ MHz}, 72 \text{ MHz}, 74.25 \text{ MHz}$
INCK Low level pulse width	t_{WLINCK}	4	—	—	ns	
INCK High level pulse width	t_{WHINCK}	4	—	—	ns	
INCK clock duty	—	45	50	55	%	Define with $0.5 \times OV_{DD}$
INCK Rise time	Tr_inck	—	—	5	ns	20 % to 80 %
INCK Fall time	Tf_inck	—	—	5	ns	80 % to 20 %


* The INCK fluctuation affects the frame rate.

INCK 13.5 MHz, 18 MHz, 24 MHz, 27 MHz, 36 MHz

Item	Symbol	Min.	Typ.	Max.	Unit	Remarks
INCK clock frequency	f_{INCK}	13.5	—	36	MHz	$f_{INCK} = 13.5 \text{ MHz}, 18 \text{ MHz}, 24 \text{ MHz}, 27 \text{ MHz}, 36 \text{ MHz}$
INCK Low level pulse width	t_{WLINCK}	5	—	—	ns	
INCK High level pulse width	t_{WHINCK}	5	—	—	ns	
INCK clock duty	—	45	50	55	%	Define with $0.5 \times OV_{DD}$
INCK Rise time	Tr_inck	—	—	5	ns	20 % to 80 %
INCK Fall time	Tf_inck	—	—	5	ns	80 % to 20 %


* The INCK fluctuation affects the frame rate.

System Clear (XCLR)



Item	Symbol	Min.	Typ.	Max.	Unit	Remarks
XCLR Low level pulse width	t_{WLXCLR}	100	—	—	ns	
XCLR Rise time	Tr_xclr	—	—	5	ns	20 % to 80 %
XCLR Fall time	Tf_xclr	—	—	5	ns	80 % to 20 %

Maison Technologies Ltd.
Internal use only

XVS / XHS Input Characteristics in Slave Mode (XMASTER pin = High)

Item	Symbol	Min.	Typ.	Max.	Unit	Remarks
XHS Low level pulse width	t_{WLXHS}	$4 / f_{INCK}$	—	—	ns	
XHS High level pulse width	t_{WHXHS}	$4 / f_{INCK}$	—	—	ns	
XVS to XHS fall width	t_{HFDLY}	$1 / f_{INCK}$	—	—	ns	
XHS to XVS rise width	t_{VRDLY}	$1 / f_{INCK}$	—	—	ns	
XVS Rise time	Tr_xvs	—	—	5	ns	20 % to 80 %
XVS Fall time	Tf_xvs	—	—	5	ns	80 % to 20 %
XHS Rise time	Tr_xhs	—	—	5	ns	20 % to 80 %
XHS Fall time	Tf_xhs	—	—	5	ns	80 % to 20 %


XVS / XHS Output Characteristics in Master Mode (XMASTER pin = Low)

* XVS and XHS cannot be used for the sync signal to pixels.

Be sure to detect sync code to detect the start of effective pixels in 1 line.

For the output waveforms in master mode, see the item of "Slave Mode and Master Mode"

Serial Communication

I²CI²C Specification

Item	Symbol	Min.	Typ.	Max.	Unit	Remarks
Low level input voltage	V _{IL}	-0.3	—	0.3 × OV _{DD}	V	
High level input voltage	V _{IH}	0.7 × OV _{DD}	—	1.9	V	
Low level output voltage	V _{OL}	0	—	0.2 × OV _{DD}	V	OV _{DD} < 2 V, Sink 3 mA
High level output voltage	V _{OH}	0.8 × OV _{DD}	—	—	V	
Input current	I _i	-10	—	10	μA	0.1 × OV _{DD} – 0.9 × OV _{DD}
Input Capacitance for SCL / SDA	C _i	—	—	10	pF	

I²C AC Characteristics (Standard-mode, Fast-mode)

Item	Symbol	Min.	Typ.	Max.	Unit	Remarks
SCL clock frequency	f _{SCL}	0	—	400	kHz	
Hold time (Start Condition)	t _{HD;STA}	0.6	—	—	μs	
Low period of the SCL clock	t _{LOW}	1.3	—	—	μs	
High period of the SCL clock	t _{HIGH}	0.6	—	—	μs	
Set-up time (Repeated Start Condition)	t _{SU;STA}	0.6	—	—	μs	
Data hold time	t _{HD;DAT}	0	—	0.9	μs	
Data set-up time	t _{SU;DAT}	100	—	—	ns	
Rise time of both SDA and SCL signals	t _r	—	—	300	ns	
Fall time of both SDA and SCL signals	t _f	—	—	300	ns	
Set-up time (Stop Condition)	t _{SU;STO}	0.6	—	—	μs	
Bus free time between a STOP and START Condition	t _{BUF}	1.3	—	—	μs	
Output fall time	t _{of}	—	—	250	ns	Load 10 pF to 400 pF, 0.7 × OV _{DD} to 0.3 × OV _{DD}











I²C AC Characteristics (Fast-mode Plus)

Item	Symbol	Min.	Typ.	Max.	Unit	Remarks
SCL clock frequency	f _{SCL}	0	—	1000	kHz	INCK ≥ 16 MHz
Hold time (Start Condition)	t _{HD;STA}	0.26	—	—	μs	
Low period of the SCL clock	t _{LOW}	0.5	—	—	μs	
High period of the SCL clock	t _{HIGH}	0.26	—	—	μs	
Set-up time (Repeated Start Condition)	t _{SU;STA}	0.26	—	—	μs	
Data hold time	t _{HD;DAT}	0	—	0.9	μs	
Data set-up time	t _{SU;DAT}	50	—	—	ns	
Rise time of both SDA and SCL signals	t _r	—	—	120	ns	
Fall time of both SDA and SCL signals	t _f	—	—	120	ns	
Set-up time (Stop Condition)	t _{SU;STO}	0.26	—	—	μs	
Bus free time between a STOP and START Condition	t _{BUF}	0.5	—	—	μs	
Output fall time	t _{of}	—	—	120	ns	Load 10 pF to 400 pF, 0.7 × OV _{DD} to 0.3 × OV _{DD}

Maison Technologies Ltd.
Internal use only

I/O Equivalent Circuit Diagram

□: External pin

Symbol	Equivalent circuit	Symbol	Equivalent circuit
TENABLE		XVS XHS	
XMASTER		VRHT VRLF VRLSTR	
XCLR INCK		SLAMODE0 SLAMODE1	
SDA SCL		DMOxP DMOxN DCKxP DCKxN	
VLOADLM TVMON1 TVMON2		TOUTx	

Spectral Sensitivity Characteristics

(Characteristics in the wafer status)




Image Sensor Characteristics

($AV_{DD} = 3.3\text{ V}$, $OV_{DD} = 1.8\text{ V}$, $DV_{DD} = 1.1\text{ V}$, $T_j = 60\text{ }^{\circ}\text{C}$, All-pixel mode, 12 bit 30 frame/s, Gain: 0 dB)

Item		Symbol	Min.	Typ.	Max.	Unit	Measurement method	Remarks
G sensitivity		S	13499 (3009)	15886 (3541)	—	Digit/lx/s (mV/lx/s)	1	F5.6 12 bit converted value HCG mode
			5199 (1159)	6119 (1364)	—	Digit/lx/s (mV/lx/s)		F5.6 12 bit converted value LCG mode
Sensitivity ratio	R / G	RG	0.5	—	0.64	—	2	—
	B / G	BG	0.34	—	0.48	—		
Saturation signal		Vsat	3895 (868)	—	—	Digit (mV)	3	12 bit converted value LCG mode
Video signal shading		SH	—	—	25	%	4	—
Vertical line		VL	—	—	90	μV	5	12 bit converted value LCG mode
Dark signal		Vdt	—	—	0.67 (0.15)	Digit (mV)	6	1/30 s storage 12 bit converted value LCG mode
Dark signal shading		ΔVdt	—	—	0.67 (0.15)	Digit (mV)	7	1/30 s storage 12 bit converted value LCG mode
Conversion efficiency ratio		Rcg	2.4	2.7	2.9	—	8	HCG mode / LCG mode

- Note)
1. Converted value into mV using 1Digit = 0.2229 mV for 12-bit output and 1Digit = 0.8916 mV for 10-bit output.
 2. The video signal shading is the measured value in the wafer status (including color filter) and does not include characteristics of the seal glass.
 3. The characteristics above apply to effective pixel area.


Image Sensor Characteristics Measurement Method

Measurement Conditions

1. In the following measurements, the device drive conditions are at the typical values of the bias conditions and clock voltage conditions.
2. In the following measurements, spot pixels are excluded and, unless otherwise specified, the optical black (OB) level is used as the reference for the signal output.

Color Coding of Physical Pixel Array

The primary color filters of this image sensor are arranged in the layout shown in the figure below. Gr and Gb represent the G signal on the same line as the R and B signals, respectively. The R signal and Gr signal lines and the Gb signal and B signal lines are output successively.



Color Coding Diagram

Definition of standard imaging conditions

- ◆ Standard imaging condition I:
Using a purple excitation LED light source with a color temperature of 2850 K, an IR cut filter CM700 ($t = 1.0$ mm) is placed between the LED light source and the sensor receiving surface to irradiate substantially parallel light.
- ◆ Standard imaging condition II:
Image a light source (color temperature of 3200 K) with a uniformity of brightness within 2 % at all angles. Use a testing standard lens with CM700 ($t = 1.0$ mm) as an IR cut filter. The luminous intensity is adjusted to the value indicated in each testing item by the lens diaphragm.
- ◆ Standard imaging condition III:
Image a light source (color temperature of 3200 K) with a uniformity of brightness within 2 % at all angles. Use a testing standard lens with CM700 ($t = 1.0$ mm) as an IR cut filter. The luminous intensity is adjusted to the value indicated in each testing item by the lens diaphragm.

Measurement Method

1. Sensitivity

Set the measurement condition to the standard imaging condition I, and calculate using the illuminance (Ev) of the sensor receiving surface, the signal values (VGr, VGb, VR, VB) at the center of the screen, and the integration time (T).

$$VG = (VGr + VGb) / 2$$

$$S = VG / (Ev \times T) \text{ [Digit / (lx} \cdot \text{s)]}$$

2. Sensitivity ratio

By using the R and B signal outputs (VR, VB) obtained from the sensitivity measurement, substitute the values into the following formulas.

$$RG = VR / VG$$

$$BG = VB / VG$$

3. Saturation signal

Set the measurement condition to the standard imaging condition II. After adjusting the luminous intensity to 20 times the intensity with the average value of the Gr and Gb signal outputs, 300 mV, measure the minimum values of the Gr, Gb, R and B signal outputs.

4. Video signal shading

Set the measurement condition to the standard imaging condition III. With the lens diaphragm at F2.8, adjust the luminous intensity so that the average value of the Gr and Gb signal outputs is 300 mV. Then measure the maximum value (Gmax [mV]) and the minimum value (Gmin [mV]) of the Gr and Gb signal outputs, and substitute the values into the following formula.

$$SH = (Gmax - Gmin) / 300 \times 100 \text{ [%]}$$

5. Vertical Line

With the device junction temperature of 60 °C and the device in the light-obstructed state, calculates each average output of Gr, Gb, R and B on respective columns. Calculates maximum value of difference with adjacent column on the same color (VL [μV]).

6. Dark signal

With the device junction temperature of 60 °C and the device in the light-obstructed state, divide the output difference between 1/30 s integration and 1/300 s integration by 0.9, and calculate the signal output converted to 1/30 s integration. Measure the average value of this output (Vdt [mV]).

7. Dark signal shading

After the measurement item 6, measure the maximum value (Vdmax [mV]) and the minimum value (Vdmin [mV]) of the dark signal output, and substitute the values into the following formula.

$$\Delta Vdt = Vdmax - Vdmin \text{ [mV]}$$

8. Conversion efficiency ratio


Set the measurement condition to the standard imaging condition II. After adjusting the average value of the Gr and Gb signal outputs to 500 mV at the LCG mode, measure the average values of Gr and Gb signal output and calculate the ratio between HCG mode and LCG mode.

Setting Registers Using Serial Communication

This sensor can write and read the setting values of the various registers shown in the Register Map by I²C communication. See the Register Map for the addresses and setting values to be set.

Description of Setting Registers (I²C)

The serial data input order is MSB-first transfer. The table below shows the various data types and descriptions. Using SLAMODE0 and SLAMODE1 pins, SLAVE address can be changed.



Pin connection of serial communication

SLAVE Address

SLAMODE1 pin	SLAMODE0 pin	MSB							LSB
Low	Low	0	0	1	1	0	1	0	R / W
Low	High	0	0	1	0	0	0	0	R / W
High	Low	0	1	1	0	1	1	0	R / W
High	High	0	1	1	0	1	1	1	R / W

* R/W is data direction bit

R / W

R / W bit	Data direction
0	Write (Master to Sensor)
1	Read (Sensor to Master)


I²C pin description

Symbol	Pin No.	Remarks
SCL	F11	I ² C serial clock input
SDA	F12	I ² C serial data communication

Register Communication Timing (I²C)

In I²C communication system, communication can be performed during the falling edge of XVS to 4XHS. For the registers marked “V” in the item of Reflection timing, when the communication is performed in the communication period shown in the figure below, they are reflected by “Frame reflection register reflection timing”. For the registers marked “I” in the item of Reflection timing, the settings are reflected when the communication is performed.


Using REGHOLD function is recommended for register setting using I²C communication. For REGHOLD function, see “Register Transmission Setting” in “Description of Functions”.



Maison Technologies
Internal use only

Communication Protocol

I²C serial communication supports a 16-bit register address and 8-bit data message type.



From Master to Slave

From Slave to Master

Direction depend on operation

S : Start Condition

Sr : Repeated Start Condition

P : Stop Condition

A : Acknowledge

$\bar{A}$: Negative Acknowledge


R/W=

0: Write (Master → Sensor)


1: Read (Sensor → Master)

Communication Protocol


Data is transferred serially, MSB first in 8-bit units. After each data byte is transferred, A (Acknowledge) / $\bar{A}$ (Negative Acknowledge) is transferred. Data (SDA) is transferred at the clock (SCL) cycle. SDA can change only while SCL is Low, so the SDA value must be held while SCL is High. The Start condition is defined by SDA changing from High to Low while SCL is High. When the Stop condition is not generated in the previous communication phase and Start condition for the next communication is generated, that Start condition is recognized as a Repeated Start condition.



Start Condition




Stop Condition



Repeated Start Condition

After transfer of each data byte, the Master or the sensor transmits an Acknowledge / Negative Acknowledge and release (does not drive) SDA. When Negative Acknowledge is generated, the Master must immediately generate the Stop Condition and end the communication.




Acknowledge and Negative Acknowledge

Register Write and Read (I²C)

This sensor corresponds to four read modes and the two write modes.

Single Read from Random Location


The sensor has an index function that indicates which address it is focusing on. In reading the data at an optional single address, the Master must set the index value to the address to be read. For this purpose, it performs dummy write operation up to the register address. The upper level of the figure below shows the sensor internal index value, and the lower level of the figure shows the SDA I/O data flow. The Master sets the sensor index value to M by designating the sensor slave address with a write request, then designating the address (M). Then, the Master generates the start condition. The Start Condition is generated without generating the Stop Condition, so it becomes the Repeated Start Condition. Next, when the Master sends the slave address with a read request, the sensor outputs an Acknowledge immediately followed by the index address data on SDA. After the Master receives the data, it generates a Negative Acknowledge and the Stop Condition to end the communication.



Single Read from Random Location

Single Read from Current Location


After the slave address is transmitted by a write request, that address is designated by the next communication and the index holds that value. In addition, when data read/write is performed, the index is incremented by the subsequent Acknowledge/Negative Acknowledge timing. When the index value is known to indicate the address to be read, sending the slave address with a read request allows the data to be read immediately after Acknowledge. After receiving the data, the Master generates a Negative Acknowledge and the Stop Condition to end the communication, but the index value is incremented, so the data at the next address can be read by sending the slave address with a read request.



Single Read from Current Location

Sequential Read Starting from Random Location

In reading data sequentially, which is starting from an optional address, the Master must set the index value to the start of the addresses to be read. For this purpose, dummy write operation includes the register address setting. The Master sets the sensor index value to M by designating the sensor slave address with a read request, then designating the address (M). Then, the Master generates the Repeated Start Condition. Next, when the Master sends the slave address with a read request, the sensor outputs an Acknowledge followed immediately by the index address data on SDA. When the Master outputs an Acknowledge after it receives the data, the index value inside the sensor is incremented and the data at the next address is output on SDA. This allows the Master to read data sequentially. After reading the necessary data, the Master generates a Negative Acknowledge and the Stop Condition to end the communication.




Sequential Read Starting from Random Location

Sequential Read Starting from Current Location

When the index value is known to indicate the address to be read, sending the slave address with a read request allows the data to be read immediately after the Acknowledge. When the Master outputs an Acknowledge after it receives the data, the index value inside the sensor is incremented and the data at the next address is output on SDA.


This allows the Master to read data sequentially. After reading the necessary data, the Master generates a Negative Acknowledge and the Stop Condition to end the communication.



Sequential Read Starting from Current Location

Single Write to Random Location


The Master sets the sensor index value to M by designating the sensor slave address with a write request and designating the address (M). After that the Master can write the value in the designated register by transmitting the data to be written. After writing the necessary data, the Master generates the Stop Condition to end the communication.



Single Write to Random Location

Sequential Write Starting from Random Location

The Master can write a value to register address M by designating the sensor slave address with a write request, designating the address (M), and then transmitting the data to be written. After the sensor receives the write data, it outputs an Acknowledge and at the same time increments the register address, so the Master can write to the next address simply by continuing to transmit data. After the Master writes the necessary number of bytes, it generates the Stop Condition to end the communication.



Sequential Write Starting from Random Location

Register Map

Please refer to IMX678_Standard_Register_Setting excel file.

Maison Technologies Ltd.
Internal use only

Readout Drive mode

Please refer to Operating mode for Software Refalene Manual of the other file.

Image Data Output Format (CSI-2 output)


Frame Format

Each line of each image frame is output like the General Frame Format of CSI-2. The settings for each packet header are shown below.

DATA Type

Header [5:0]	Name	Setting register (I ² C)	Description
00h	Frame Start Code	N/A	FS
01h	Frame End Code	N/A	FE
12h	Embedded Data	N/A	Embedded data
2Bh	RAW10	Address: 3023h MDBIT [1:0]	Recording pixel data
2Ch	RAW12		Recording pixel data
37h	OB Data	N/A	Vertical OB line data

Frame Structure




Frame Structure of CSI-2 output


Embedded Data Line

The Embedded data line is output in a line following the sync code FS.


Embedded Data Format



RAW10



RAW12



Maison Technologies Ltd.
Internal use only


Specific output examples are shown below.

Pixel (8bit)	bit	I ² C address [HEX]	Data Byte Description	Description
1	[7:0]	—	—	ignored
2	[4:0]	3018[4:0]	WINMODE	—
3	[4:0]	—	—	ignored
	[5]	3020[0]	HREVERSE	—
	[7:4]	—	—	ignored
4 to 8	[7:0]	—	—	ignored
9	[4:0]	—	—	ignored
	[5]	3021[1]	VREVERSE	—
	[7:6]	—	—	ignored
10	[7:0]	—	—	ignored
11	[5:0]	—	—	ignored
	[7:6]	3022[1:0]	ADBIT	—
12	[0]	—	—	ignored
	[1]	301B[1:0]	HADD	—
	[2]	301B[1:0]	VADD	—
	[7:3]	—	—	ignored
13	[2:0]	3040[2:0]	LANEMODE	—
	[4:3]	3023[1:0]	MDBIT	—
	[7:4]	—	—	—
14 to 23	[7:0]	—	—	ignored
24	[7:0]	3050[7:0]	SHR0	—
25	[7:0]	3051[7:0]		
26	[3:0]	3052[3:0]		
	[7:4]	—	—	ignored
27 to 53	[7:0]	—	—	ignored
54	[7:0]	30DC[7:0]	BLKLEVEL	—
55	[1:0]	30DD[1:0]		
	[7:2]	—		
56 to 216	[7:0]	—	—	ignored


Output data is Data[7:0] = 00h from 217 to 224 pixel.

Output data is Data[7:0] = 07h from 225 to end pixel.

All-pixel mode




Pixel Array Image Drawing in All pixel mode (2,4,8 Lanes)




* It outputs in the format of RAW10 or RAW12.

- FS / FE
- Embedded data
- Ineffective OB / Blanking
- Effective OB
- Packet header / Packet footer
- Ignored area of effective pixel
- Margin for color processing
- Recording pixel area
- HB : Horizontal blanking

Drive Timing Chart in All pixel mode (2,4,8 Lanes)




Pixel Array Image Drawing in All pixel mode (4 Lane × 2ch)




Drive Timing Chart in All pixel mode (4 Lane × 2ch)

Horizontal/Vertical 2/2-line binning mode




Pixel Array Image Drawing in Horizontal /Vertical 2/2-line binning mode (2,4,8 Lanes)




* It outputs in the format of RAW10 or RAW12.

- FS / FE
- Embedded data
- Ineffective OB / Blanking
- Effective OB
- Packet header / Packet footer
- Ignored area of effective pixel
- Margin for color processing
- Recording pixel area
- VB : Vertical blanking
- HB : Horizontal blanking

Drive Timing Chart in Horizontal /Vertical 2/2-line binning mode (2,4,8 Lanes)



Pixel Array Image Drawing in Horizontal /Vertical 2/2-line binning mode (4 Lane × 2ch)



Drive Timing Chart in Horizontal /Vertical 2/2-line binning mode (4 Lane × 2ch)

Description of Various Function

Please refer to Software Reference Manual about the following function.

- ◆ Window Cropping Mode
- ◆ Standby Mode
- ◆ Slave Mode and Master Mode
- ◆ Gain Adjustment Function
- ◆ Black Level Adjustment Function
- ◆ Normal Operation and Inverted Operation
- ◆ Shutter and Integration Time Setting
- ◆ Normal Exposure Operation
- ◆ Long Exposure Operation
- ◆ Example of Integration Time Settings
- ◆ Signal Output
- ◆ CSI-2 Output
- ◆ MIPI Transmitter
- ◆ INCK Setting
- ◆ Global Timing setting
- ◆ Register Hold Setting
- ◆ Mode Transitions
- ◆ XSIZE_OVERLAP Setting

Other Function


This sensor has the function as below. About detail, refer to each application note.

- Digital Overlap HDR (Combining 2-frame, 3-frame)
- Additional Function of Synchronizing Sensors
- Clear HDR

Power-on and Power-off Sequence

Power-on sequence

1. Turn On the power supplies so that the power supplies rise in order of 1.1 V power supply (DV_{DD}) → 1.8 V power supply (OV_{DD}) → 3.3 V power supply (AV_{DD}). In addition, all power supplies should finish rising within 200 ms.
2. The register values are undefined immediately after power-on, so the system must be cleared. Hold XCLR at Low level for 500 ns or more after all the power supplies have finished rising. (The register values after a system clear are the default values.)
3. The system clear is applied by setting XCLR to High level. The master clock input after setting the XCLR pin to High level.
4. Make the sensor setting by register communication after the system clear.




Power-on Sequence

Item	Symbol	Min.	Max.	Unit
1.1 V power supply rising → 1.8 V power supply rising	T_0	0	—	ns
1.8 V power supply rising → 3.3 V power supply rising	T_1	0	—	ns
Rising time of all power supply	T_2	—	200	ms
3.3 V power supply rising → Clear OFF	T_{LOW}	500	—	ns
Clear OFF → INCK rising	T_3	1	—	μ s
Clear OFF → Communication start	T_4	20	—	μ s
Standby OFF (communication) → External input XHS, XVS (slave mode only)	T_{SYNC}	24	—	ms

Slew Rate Limitation of Power-on Sequence

Conform the slew rate limitation shown below when power supply change 0 V to each voltage (0 % to 100 %) in power-on sequence.




Item	Symbol	Power supply	Min.	Max.	Unit	Remarks
Slew rate	SR	DV _{DD} (1.1 V)	—	25	mV/ μ s	
		OV _{DD} (1.8 V)	—	25	mV/ μ s	
		AV _{DD} (3.3 V)	—	25	mV/ μ s	

Maison Technologies Ltd.
Internal use only

Power-off sequence

Turn Off the power supplies so that the power supplies fall in order of 3.3 V power supply (AV_{DD}) → 1.8 V power supply (OV_{DD}) → 1.1 V power supply (DV_{DD}). In addition, all power supplies should be falling within 200 ms. Set each digital input pin (INCK, SDA, SCL, XCLR, XVS, XHS, SLAMODE0, SLAMODE1) to 0 V before the 1.8 V power supply (OV_{DD}) falls.



Power-off Sequence

Item	Symbol	Min.	Max.	Unit
Standby ON (communication) → LP11 mode start	T_{STB}	FE		—
LP00 → XCLR falling	T_{CLR}	128	—	cycle
3.3 V power shut down → 1.8 V power shut down	T_5	0	—	ns
1.8 V power shut down → 1.1 V power shut down	T_6	0	—	ns
Shut down time of all power supply	T_7	—	200	ms

Sensor Setting Flow


Setting Flow in Sensor Slave Mode

The figure below shows operating flow in sensor slave mode.

For details of "Power-on" to "Reset cancel", see the item of "Power-on sequence" in this section.

For details of "Standby cancel" until "Wait for image stabilization", see the item of "Standby mode".

"Standby setting (power save mode)" can be made by setting the STANDBY register to "1" during "Operation".



Sensor Setting Flow (Sensor Slave Mode)

Setting Flow in Sensor Master Mode


The figure below shows operating flow in sensor master mode.

For details of "Power-on" to "Reset cancel", see the item of "Power on sequence" in this section.

For details of "Standby cancel" until "Wait for image stabilization", see the item of "Standby mode".




In master mode, "Master mode start" by setting register XMSTA to "0" after "Waiting for internal regulator stabilization"

"Standby setting (power save mode)" can be made by setting the STANDBY register to "1" during "Operation". This time set "master mode stop" by setting XMSTA to "1".



Sensor Setting Flow (Sensor Master Mode)

Peripheral Circuit



Application circuits shown are typical examples illustrating the operation of the devices.

Sony Semiconductor Solutions Corporation cannot assume responsibility for any problems arising out of the use of these circuits or for any infringement of third party and other right due to same.

Spot Pixel Specifications

($AV_{DD} = 3.3\text{ V}$, $OV_{DD} = 1.8\text{ V}$, $DV_{DD} = 1.1\text{ V}$, $T_j = 60\text{ }^{\circ}\text{C}$, 30 frame/s, Gain: 0 dB)

Type of distortion	Level	Maximum distorted pixels in each zone				Measurement method	Remarks
		II'	Effective OB	III	Ineffective OB		
Black or white pixels at high light	$30\% \leq D$	90	No evaluation criteria applied			1	
White pixels in the dark	$5.6\text{ mV} \leq D$	800		No evaluation criteria applied		2	1/30 s storage

Note) 1. Zone is specified based on all-pixel drive mode
2. D Spot pixel level

Zone Definition

(1, 1)	10	OB side ignored area	
(1, 11)	10	Vertical effective OB	V.OB (3856, 20)
(1, 21)	4	Ignored area of effective pixel	ZoneIII
(1, 25)			ZoneII'
			(3856, 2200)

Notice on White Pixels Specifications

After delivery inspection of CMOS image sensors, particle radiation such as cosmic rays etc. may distort pixels of CMOS image sensors, and then distorted pixels may cause white point effects in dark signals in picture images. (Such white point effects shall be hereinafter referred to as "White Pixels".)

Unfortunately, it is not possible with current scientific technology for CMOS image sensors to prevent such White Pixels. It is recommended that when you use CMOS image sensors, you should consider taking measures against such White Pixels, such as adoption of automatic compensation systems for White Pixels in dark signals and establishment of quality assurance standards.

Unless the Seller's liability for White Pixels is otherwise set forth in an agreement between you and the Seller, Sony Semiconductor Solutions Corporation or its distributors (hereinafter collectively referred to as the "Seller") will, at the Seller's expense, replace such CMOS image sensors, in the event the CMOS image sensors delivered by the Seller are found to be to the Seller's satisfaction, to have over the allowable range of White Pixels as set forth above under the heading "Spot Pixels Specifications", within the period of three months after the delivery date of such CMOS image sensors from the Seller to you; provided that the Seller disclaims and will not assume any liability after you have incorporated such CMOS image sensors into other products.

Please be aware that Seller disclaims and will not assume any liability for (1) CMOS image sensors fabricated, altered or modified after delivery to you, (2) CMOS image sensors incorporated into other products, (3) CMOS image sensors shipped to a third party in any form whatsoever, or (4) CMOS image sensors delivered to you over three months ago. Except the above mentioned replacement by Seller, neither Sony Semiconductor Solutions Corporation nor its distributors will assume any liability for White Pixels. Please resolve any problem or trouble arising from or in connection with White Pixels at your costs and expenses.

[For Your Reference] The Annual Number of White Pixels Occurrence

The chart below shows the predictable data on the annual number of White Pixels occurrence in a single-story building in Tokyo at an altitude of 0 meters. It is recommended that you should consider taking measures against the annual White Pixels, such as adoption of automatic compensation systems appropriate for each annual number of White Pixels occurrence.

The data in the chart is based on records of past field tests, and signifies estimated number of White Pixels calculated according to structures and electrical properties of each device. Moreover, the data in the chart is for your reference purpose only, and is not to be used as part of any CMOS image sensor specifications.

Example of Annual Number of Occurrence

White Pixel Level (in case of integration time = 1/30 s) (T _J = 60 °C)	Annual number of occurrence
5.6 mV or higher	16 pcs
10.0 mV or higher	11 pcs
24.0 mV or higher	6 pcs
50.0 mV or higher	3 pcs
72.0 mV or higher	3 pcs

Note 1) The above data indicates the number of White Pixels occurrence when a CMOS image sensor is left for a year.

Note 2) The annual number of White Pixels occurrence fluctuates depending on the CMOS image sensor storage environment (such as altitude, geomagnetic latitude and building structure), time (solar activity effects) and so on. Moreover, there may be statistic errors. Please take notice and understand that this is an example of test data with experiments that have being conducted over a specific time period and in a specific environment.

Note 3) This data does not guarantee the upper limits of the number of White Pixels occurrence.


Measurement Method for Spot Pixels

After setting to standard imaging condition II, and the device driver should be set to meet bias and clock voltage conditions. Configure the drive circuit according to the example and measure.

1. Black or white pixels at high light

After adjusting the luminous intensity so that the average value V_G of the Gb / Gr signal outputs is 548 mV, measure the local dip point (black pixel at high light, V_{iB}) and peak point (white pixel at high light, V_{iK}) in the Gr / Gb / R / B signal output V_i ($i = \text{Gr} / \text{Gb} / \text{R} / \text{B}$), and substitute the value into the following formula.

$$\text{Spot pixel level } D = ((V_{iB} \text{ or } V_{iK}) / \text{Average value of } V_i) \times 100 [\%]$$



Signal output waveform of R / G / B channel



2. White pixels in the dark

Set the device to a dark setting and measure the local peak point of the signal output waveform, using the average value of the dark signal output as a reference.

Spot Pixel Pattern Specification

White Pixel, Black Pixel and Bright Pixel are judged from the pattern whether they are allowed or rejected and counted.

List of White Pixel, Black Pixel and Bright Pixel Pattern

No.	Pattern 	White pixel Black pixel Bright pixel
1		Rejected
2		Rejected

Note) 1. “●” shows the position of white pixel, black pixel, or bright pixel.


Each pattern is defined by three white pixels, three black pixels, or three bright pixels.

(Example: If one black pixel and two white pixels are located like pattern No.1, they are not judged to be rejected.)

2. Products that have one or more rejected patterns are filtered out.

3. All spot pixels are subject to the “Maximum distorted pixels in each zone” judgment in the section of “Spot Pixel Specifications” even if they do not correspond to the patterns in the table above.

Marking



Note: One character of alphabet or number shall be placed from V to Z part. (Plating option)

DRAWING No. AM-C678AAQR1 (2D)

Notes On Handling

1. Static charge prevention

Image sensors are easily damaged by static discharge. Before handling be sure to take the following protective measures.

- (1) Either handle bare handed or use non-chargeable gloves, clothes or material.
Also use conductive shoes.
- (2) Use a wrist strap when handling directly.
- (3) Install grounded conductive mats on the floor and working table to prevent the generation of static electricity.
- (4) Ionized air is recommended for discharge when handling image sensors.
- (5) For the shipment of mounted boards, use boxes treated for the prevention of static charges.

2. Protection from dust and dirt

Image sensors are packed and delivered with care taken to protect the element glass surfaces from harmful dust and dirt. Clean glass surfaces with the following operations as required before use.

- (1) Perform all lens assembly and other work in a clean environment (class 1000 or less).
- (2) Do not touch the glass surface with hand and make any object contact with it.
If dust or other is stuck to a glass surface, blow it off with an air blower.
(For dust stuck through static electricity, ionized air is recommended.)
- (3) Clean with a cotton swab with ethyl alcohol if grease stained. Be careful not to scratch the glass.
- (4) Keep in a dedicated case to protect from dust and dirt. To prevent dew condensation, preheat or precool when moving to a room with great temperature differences.
- (5) When a protective tape is applied before shipping, remove the tape applied for electrostatic protection just before use. Do not reuse the tape.

3. Installing (attaching)


- (1) If a load is applied to the entire surface by a hard component, bending stress may be generated and the package may fracture, etc., depending on the flatness of the bottom of the package.
Therefore, for installation, use either an elastic load, such as a spring plate, or an adhesive.
- (2) The adhesive may cause the marking on the rear surface to disappear.
- (3) If metal, etc., clash or rub against the package surface, the package may chip or fragment and generate dust.
- (4) Acrylate anaerobic adhesives are generally used to attach this product. In addition, cyanoacrylate instantaneous adhesives are sometimes used jointly with acrylate anaerobic adhesives to hold the product in place until the adhesive completely hardens. (Reference)
- (5) Note that the sensor may be damaged when using ultraviolet ray and infrared laser for mounting it.

4. Reflow soldering conditions

The following items should be observed for reflow soldering.

(1) Recommended temperature profile for reflow soldering

Control item	Profile (at part side surface)
1. Preheating	150 to 180 °C 60 to 120 s
2. Temperature up (down)	+4 °C/s or less (- 6 °C/s or less)
3. Reflow temperature	Over 230 °C 10 to 30 s Max. 5 °C/s
4. Peak temperature	Max. 240 ± 5 °C



(2) Reflow conditions

- Make sure the temperature of the upper surface of the seal glass resin adhesive portion of the package does not exceed 245 °C.
- Perform the reflow soldering only one time.
- Finish reflow soldering within 72 h after unsealing the degassed packing.
Store the products under the condition of temperature of 30 °C or less and humidity of 70 % RH or less after unsealing the package.
- Perform re-baking only one time under the condition at 125 °C for 24 h.
- Note that condensation on glass or discoloration on resin interfaces may occur if the actual temperature and time exceed the conditions mentioned above.

(3) Others


- Carry out evaluation for the solder joint reliability in your company.
- After the reflow, the paste residue of protective tape may remain around the seal glass.
(The paste residue of protective tape should be ignored except remarkable one.)
- Note that X-ray inspection may damage characteristics of the sensor.

5. Others

- Do not expose to strong light (sun rays) for long periods, as the color filters of color devices will be discolored.
- Exposure to high temperature or humidity will affect the characteristics. Accordingly avoid storage or use in such conditions.
- This product is precision optical parts, so care should be taken not to apply excessive mechanical shocks or force.
- Note that imaging characteristics of the sensor may be affected when approaching strong electromagnetic wave or magnetic field during operation.
- Note that image may be affected by the light leaked to optical black when using an infrared cut filter that has transparency in near infrared ray area during shooting subjects with high luminance.
- Please perform the tilt adjustment for the optical axis in your company as required.

Package Outline

(Unit: mm)



- 1) "A" is the center of the effective image area
- 2) Base level "S" is a virtual flat surface calculated at three points (A12, N1, N12) of back side terminal
- 3) The rotation angle of the effective image area relative to "X" and "Y" is $\pm 1^\circ$
- 4) The tilt of the effective image area relative to the bottom "Z" is less than 0.05mm
- 5) The thickness of the cover glass is 0.5mm
- 6) Cover glass both sides are processed by AR coating
- 7) As for standard for resin overflow in package outside, it shall be accepted up to outermost line tolerance of package.
- 8) One character of alphabet or number shall be placed from W to Z part.
(Plating option)

PACKAGE STRUCTURE

CLASSIFICATION	LGA
LEAD TREATMENT	GOLD PLATING
PIN NUMBER	132Pin
PACKAGE WEIGHT (Typ.)	0.95g
DRAWING NUMBER	AS-C114 (E)

List of Trademark Logos and Definition Statements

STARVIS 2

* STARVIS 2 is a registered trademark or trademark of Sony Group Corporation or its affiliates. The STARVIS 2 is back-illuminated pixel technology used in CMOS image sensors for security camera applications. It features a sensitivity of 2000 mV or more per $1 \mu\text{m}^2$ (color product, when imaging with a 706 cd/m^2 light source, F5.6 in 1 s accumulation equivalent). It also has a wide dynamic range (AD 12 bit) of more than 8 dB compared to STARVIS for the same pixel size in a single exposure, and achieves high picture quality in the visible-light and near infrared light regions.

Maison Technologies Ltd.
Internal use only

Revision History

Date of change	Revision	Page	Description
2021/04/23	0.1	—	First Edition
2021/11/26	E21Y08	ALL	Correction: Dual Gain HDR -> Clear HDR
		ALL	Correction: Fixed "TBD" CDS / PGA function Current Consumption Spectral Sensitivity Characteristics Image Sensor Characteristics Measurement Method Sensor Setting Flow Spot Pixel Specifications Notice on White Pixels Specifications Measurement Method for Spot Pixels Spot Pixel Pattern Specification
		1, 55	Correction: STARVIS -> STARVIS2. Trademark Logos and Definition Statements
		1	Deleted: part of the sentence in Description (Applications: Security cameras, FA cameras, Industrial cameras) -> (Application: Security cameras)
		1, 16	Correction: Input frequency 6 to 27 MHz -> 13.5 MHz / 18 MHz / 24 MHz / 27 MHz / 36 MHz
		1	Correction: part of the sentence in Features Variable-speed shutter function (resolution 2H units) -> Variable-speed shutter function (resolution 1H unit)
		8, 36, 47	Correction: Valuer of OB area Ignored OB: 8 -> 10 Vertical effective OB: 12 -> 10
		15	Correction: Current Consumption Operating current Max. value
		37, 38, 39	Added: Pixel Array Image Drawing and Drive Timing Chart
		51	Correction: Marking TENTATIVE -> AM-C678AAQR1(2D)
		54	Correction: Package Outline TENTATIVE -> AS-C114(E)